AXPPC-215A-CP1 Touch Panel PC Industrial Touchscreen Panel PC





Feature:

- ◇ Pure metal, fanless design
- ◇ Onboard Intel 12th Core I5/I7
- ◇ Support 6*COM, 8*Isolated GPIO
- ◇ Support 3*Intel Lan(LAN1~2: Gigabit Ethernet, LAN3:2.5G);
- ◇ Support 9～36V input (Reverse protection);
- ◇ IP65 protection at front panel
- ◇ Applied OS：

Specification

Model		AXPPC-215A-CP1
Screen parameters	Size	21.5 inch
	Ratio	16:9
	Resolution	1920*1080
	Brightness	250cd/㎡
	Touch	Resistive/Capacitive option
Machine Size		540*332*60mm
Embedded size		528 * 320 mm
weight		6.8KG
Temp		0℃～+50℃
Humidity		5% ～ 95%Non-condensing
Color		Gray
Material		Aluminum & Steel
Processor		Intel Core i5-1235U/i7-1255U
Memory		1*DDR5 4800MHz SODIMM, up to 32GB
BIOS		AMI BIOS
Display Chip		Integrated Intel UHD Graphics
Display port		1*HDMI, 1*JHDMI(optional), 1*LVDS(already connected LCD), Support 3 display
Storage		2*M.2 2280(1*NVMe+SATA, 1*NVMe), 1*2.5 inch SSD/HDD
Expansion		Support 1*Mini PCIE(Support WiFi/BT/4G, with SIM slot), 1*M.2 E-Key slot;
I/O port		1* power button, 1*2*2pin PW phoenix connector, 1*CMOS, 1*2pin Power Supply 1*HDMI, 4*USB3.0, 2*1000M Lan, 1*2.5G Lan, 1* Audio 6*COM(Com3, Com4 can be RS232/RS485 option), GPIO(4 in and 4 out)
Others		TPM2.0、electricity boot、on time boot、wake on lan、PXE、WDT（0～255 level）
Expand function		USB2.0 x1, GPIO2, HDMI2; (standard product don't have it, need to be customized)
Speaker		2*4Ω 2W speaker
Input Voltage		DC 9～36V wide voltage input, support Reverse polarity protection
Certifications		CE、 CCC、 FCC ClassA、 RoHS
Application		Automation, Medical，Transportation，Warehouse，Machine Vision

AXPPC-215A-CP1 Drawing

